

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
4 January 2001 (04.01.2001)

PCT

(10) International Publication Number
WO 01/01082 A1(51) International Patent Classification⁷: **G01F 1/68,**
A01K 1/00**JANSSENS, Karl, Hans, Bert [BE/BE];** Tervuursesteen-
weg 178, B-3001 Heverlee (BE).(21) International Application Number: **PCT/IB00/00865**(74) Agent: **PRINS, A., W.;** Vereenigde, Nieuwe Parklaan 97,
NL-2587 BN The Hague (NL).

(22) International Filing Date: 28 June 2000 (28.06.2000)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1012459 28 June 1999 (28.06.1999) NL(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.(71) Applicant (*for all designated States except US*):
KATHOLIEKE UNIVERSITEIT LEUVEN [BE/BE];
Groot Begijnhof 59, B-3000 Leuven (BE).(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): **BERCKMANS,**
Daniel, Albert [BE/BE]; Slangenstraat 37, B-3010
Kessel-Lo (BE). **VRANKEN, Erik, Joannes, Matheus**
[BE/BE]; Molendijkstraat 151, B-3582 Beringen (BE).

Published:

— With international search report.

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR DETERMINING A FLOW PATTERN OF A FLUID IN A SPACE



(57) Abstract: A method for determining a flow pattern of a gas in a space, wherein: gas is passed via at least one inlet into the space, in a first position, at a distance from the at least one inlet a temperature distribution, at any rate at least two temperatures in at least a part of the gas stream is measured, on the basis of the measured temperature distribution, at least of the measured temperatures the position of the maximum or minimum temperature is determined, and on the basis of at least the position of this maximum or minimum temperature the flow pattern in the space is determined, preferably by means of an algorithm.

WO 01/01082 A1